



C-MAG MS 10 IKAMAG®

New magnetic stirrer without heating. With ceramic set-up plate which offers excellent chemical resistance.

- Powerful motor for stirring quantities of up to 15 l (H₂O)
- Elevated control panel for protection against leaking liquids

Accessories: IKAFLON® 10 Magnetic stirring bar, IKAFLON® 15 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 40 Magnetic stirring bar, IKAFLON® 50 Magnetic stirring bar, IKAFLON® 80 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, TRIKA® 40 Magnetic stirring bar, RS 1 Set of magnetic stirring bars, RSE Stirring bar remover, H 16 V Support rod

Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	15
Stirring quantity max. (H ₂ O) [l]	15
Motor rating input [W]	15
Motor rating output [W]	1.5
Speed display	scale
Speed range [1/min]	100 - 1500
Stirring bar length max. [mm]	80
Speed control	scale 0 - 6
Set-up plate material	ceramic
Set-up plate dimensions [mm]	260 x 260
Dimensions (W x H x D) [mm]	300 x 105 x 415
Weight [kg]	6
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	230
Frequency [Hz]	50/60
Power input [W]	30
Ident. No.	3582600