

## Data Sheet

Mixing / Magnetic Stirrers



### Mini MR standard IKAMAG®

The improvement of the magnetic stirrer. new: For stirring quantities up to 1.000 ml (H<sub>2</sub>O)  
 new: Infinitely variable speed from 0 - 2.500 rpm  
 - White set-up plate suitable for observing color reactions

Accessories: TRIKA® 25 Magnetic stirring bar, RSE Stirring bar remover, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, IKAFLON® 15 Magnetic stirring bar

#### Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H <sub>2</sub> O) [l]	1
Stirring quantity max. (H <sub>2</sub> O) [l]	1
Motor rating input [W]	3
Motor rating output [W]	2
Speed display	none
Speed range [1/min]	0 - 2500
Stirring bar length max. [mm]	30
Set-up plate material	polyester
Set-up plate dimensions [mm]	115 x 115
Dimensions (W x H x D) [mm]	114 x 37 x 127
Weight [kg]	0.25
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 42
RS 232 interface	no
Analog output	no
Voltage [V]	100 - 240
Frequency [Hz]	50/60
Power input [W]	3
DC Voltage [V=]	12
Power input [mA]	300
<b>Ident. No.</b>	<b>3674000</b>