



C-MAG HS 4 IKAMAG®

New magnetic stirrer with heating and ceramic heating plate which offers excellent chemical resistance.

- Powerful motor for stirring quantities of up to 5 l (H₂O)
- Fixed safety circuit of 550 °C
- Hot Top indicator >> hot surface warning to prevent burns!
- Exact temperature setting via digital display (LED)
- Digital error code display
- Elevated control panel for protection against leaking liquids

Accessories: H 38 Holding rod, H 44 Boss head clamp, IKAFLON® 10 Magnetic stirring bar, IKAFLON® 15 Magnetic stirring bar, IKAFLON® 20 Magnetic stirring bar, IKAFLON® 25 Magnetic stirring bar, IKAFLON® 30 Magnetic stirring bar, TRIKA® 25 Magnetic stirring bar, RS 1 Set of magnetic stirring bars, RSE Stirring bar remover, H 16 V Support rod

Technical Data

Number of stirring positions	1
Stirring quantity max. per stirring position (H ₂ O) [l]	5
Stirring quantity max. (H ₂ O) [l]	5
Motor rating input [W]	15
Motor rating output [W]	1.5
Speed display	scale
Speed range [1/min]	100 - 1500
Heat output [W]	250
Heating rate (1 l H ₂ O in H15) [K/min]	2.5
Heating temperature range [°C]	50 - 500
Heat control	LED
Heat control accuracy [±K]	10
Speed control	scale 0 - 6
Fixed safety circuit [°C]	550
Set-up plate material	ceramic
Set-up plate dimensions [mm]	100 x 100
Dimensions (W x H x D) [mm]	150 x 105 x 260
Weight [kg]	3
Permissible ambient temperature [°C]	5 - 40
Permissible relative moisture [%]	80
Protection class according to DIN EN 60529	IP 21
Voltage [V]	230
Frequency [Hz]	50/60
Power input [W]	270
Ident. No.	3581000